

## How to apply PotHoleGlue™

Follow instructions below for a successful pothole repair.

1. Pour the recycled asphalt (RAP) into a wheelbarrow. ½" minus aggregate with 20% fines may be substituted when RAP is not available.
2. Mix the dry PotHoleGlue into the recycled asphalt. (For smaller potholes, use the amount of recycled asphalt needed and add the equivalent amount of the dry PotHoleGlue. Make sure to reseal the plastic bag for future use).
3. Evenly distribute 0.4 gallons of water over the dry mix (**Do not over water!**).
4. **Thoroughly** mix water with the blend of PotHoleGlue and recycled asphalt until you have a homogenous pothole patch. Patch might appear somewhat dry; however, this consistency is needed for best compaction.
5. Pour the patch into the pothole and compact it with a hand tamper, plate compactor or similar equipment.
6. Clean wheelbarrow and any other equipment with water.

Another compelling product by:

**DirtGlue**<sup>®</sup>  
ENTERPRISES

[www.dirtglue.com](http://www.dirtglue.com)

Our line of products include:

**DirtGlue**<sup>®</sup>  
Polymer Emulsion

**DustLess**<sup>™</sup>  
The Clear Alternative

**ArenaKleen**<sup>™</sup>  
The Rider's Choice

**PotHoleGlue**<sup>™</sup>  
*A Lasting Experience*

**Strong, Durable  
Pothole Repair**

Easy application

Sticks to surrounding asphalt

Multi component quality system

No special equipment needed

Environmentally friendly

Easy clean-up

**ESSI**  
**151 Kalmus Drive, Ste. A202**  
**Costa Mesa, CA 92626**

**Office: 800-588-8439**  
**Fax: 714-513-2118**  
**Email: [info@essipro.com](mailto:info@essipro.com)**

## PotHoleGlue™ is the Solution

PotHoleGlue has been specifically formulated as a multi component system producing a catalytic reaction to create a powerful, durable and easy to apply solution for a well known problem.

The highly effective dry formulation of a tough polymer, a curing enhancing element and recycled asphalt provides a unique, solid and durable structure for long-lasting pothole repairs.



## PotHoleGlue™ is Environmentally Safe

The product:

- Contains no harmful chemical solvents
- Does not emit any volatile organic compounds (VOC)
- Is non-corrosive
- Does not change the pH of the soil
- Has no harmful effects on people, plants animals, fish or other aquatic life

As a water soluble product, PotHoleGlue may be applied to environmentally sensitive areas as it has no adverse effects on plants, animals or groundwater

Considering these characteristics, PotHoleGlue is a superb alternative to conventional, more harmful and less effective methods such as cold patch.



PotHoleGlue is environmentally safe

## PotHoleGlue™ in our Repair Kit Package

PotHoleGlue is conveniently packaged as a user-friendly repair kit in a 5 gallon pail. It consists of 45 lbs. of recycled asphalt as the pothole filler and 6.5 lbs. of PotHoleGlue in a reclosable plastic bag that serves as the unique high-quality bonding agent.

This package has enough material to permanently fix a 6 square foot pothole at one inch depth.

Application is easy and straight forward by mixing the two dry components with less than 1/2 gallon of water. See detailed application instruction in this brochure.



For larger or multiple applications, PotHoleGlue can be ordered in bulk (55 lbs bags with 42 bags per pallet).

One 55 lbs bag of PotHoleGlue (in combination with recycled asphalt and/or aggregate) will cover an area of 50 square feet at 1 inch depth.

## PotHoleGlue is Unique

- Excellent bonding capabilities to fine particles, asphalt, aggregate, and other organic or inorganic substrates
- Superb curing characteristics at or above freezing temperatures
- Remarkably simple application process
- Exceptional chemical, thermal and ultraviolet light stability

Member of :



International Erosion Control Association